



MANUFACTURING? BEARING INDONESIA



6200ZZNR Bearing 2D drawings and 3D CAD models

10,000 mm x 30,000 mm x 9,000 mm 10,000
mm x 30,000 mm x 9,000 mm NTN 6200ZZNR
deep groove ball bearings

Bearing No. 6200ZZNR

Size	10x30x9 mm
Bore Diameter	10,000 mm
Outer Diameter	30,000 mm
Width	9,000 mm
d	10,000 mm
D	30,000 mm
B	9,000 mm
C	9,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.033
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	10MM Bore; 30MM



MANUFACTURING? BEARING INDONESIA

	Outside Diameter; 9MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Other Features	Deep Groove With Snap Ring Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0.071
Outer Race Width	0.354 Inch 9 Millimeter
Outside Diameter	1.181 Inch 30 Millimeter
Bore	0.394 Inch 10 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	10 mm
static load capacity:	2390 N
outside diameter:	30 mm
precision rating:	ISO Class 0
overall width:	9 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Shielded
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	9 mm



MANUFACTURING?BEARING INDONESIA

snap ring included:	With Snap Ring
outer ring width:	9 mm
internal clearance:	CN
maximum rpm (grease):	25000 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	0.6 mm
dynamic load capacity:	5100 N
manufacturer product page:	Click here